

Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, B2ca 4P, Green



Part Number:
UU009175728

The Everon™ Copper Datacom F/UTP 550/24 cable is designed up to 550MHz and its transmission characteristics exceed Category 6A specifications according to EN50288-10-1 IEC 61156-5. High system margins for the complete link according to the last version of ISO/IEC 11801 and EN 50173 (Series) will be achieved by using corresponding hardware together with this highend copper cable. The cable has a streamlined construction and low weight. Overall shielding with with a Allaminated foil and each twisted pair unshielded (F/UTP). The cable satisfies Class B interference radiation standards according to EN 55022, as well as immunity according to EN 55024, which enables the realization of CE-compatible networks.

Features and Benefits

F/UTP 550/24 copper cable specified up to 550 MHz

Fulfills all requirements of category 6A according to EN 50288-10-1 and IEC 61156-5

Ensures high system margins according ISO/IEC 11801 Ed.2.2 (2011) and EN 50173-1 series (2011)

Twisted pair, surrounded by an overall metallic foil shield

LSOH Jacket, CPR B2ca-s1a,d0,a1

Satisfies Class B + interference radiation as well as immunity standards (EN 55022 and EN 55024)

Supports Power over Ethernet (PoE / PoE+) according IEEE 802.3at

Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, B2ca 4P, Green

CORNING

Specifications

Environmental Conditions

Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

General Specifications

Environment	Indoor
Category	6A
Cable type	F/UTP
Bandwidth	550 MHz
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to fire	B2ca, s1a, d0, a1
Legacy Part Number	VOL6AFL4500
Brand	Everon™

Cable Design

Conductor	Copper Wire, AWG 24/1
Conductor insulation	Solid PE
Twisting	2 cores to a pair
Outer jacket material	LSZH™/FRNC
Outer jacket colour	Green

Mechanical Characteristics

Fire load	630 MJ/km
Nominal outer diameter	7.5 mm
Min. bend radius installation	8x Cable-Ø

Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, B2ca 4P, Green



Mechanical Characteristics	
Maximum tensile strength	80 N

Electrical Characteristics	
Conductor resistance unbalance	2 %
Delay skew	45 ns/100 m
Max. loop resistance	190 Ω/km
Propagation delay	545 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Surface transfer impedance	10 mΩ
Propagation velocity at >10 MHz (NVP*c)	69 %
Coupling attenuation	55 dB
Insulation Resistance	> 5000 MΩ*km

Ordering Information	
Product Number	UU009175728
Length	500 m
Weight	49.5 kg
Packing type	Drum
Units per delivery	1/1

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU
Approvals and Listings	IEC 61156-5; EN 50288-10-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, ANSI/TIA -568-C-2; IEC60304
Design And Test Criteria	1000 Base-T IEEE 802.3 an; PoE / PoE++ IEEE 802.3af, IEEE 802.3at
Flame propagation test	IEC 60332-1
Smoke density	IEC 61034-2

Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, B2ca 4P, Green

CORNING

Standards

Halogen content test	Zero Halogen to IEC 60754-1
Level of corrosion	Non-corrosive according to IEC 60754-2

Electrical Characteristics

Frequency [MHz]	4	10	20	63	100	250	500	550
Attenuation according to Standard [db/100m]	3.8	5.9	8.4	15.0	19.1	31.1	45.3	
Typical attenuation [db/100m]	3.6	5.5	7.9	14.5	18.5	30.0	43.0	50.0
NEXT according to Standard [db/100m]	66.3	60.3	55.8	48.4	45.3	39.3	34.8	
Typical NEXT Values [db/100m]	71.0	65.0	61.0	53.0	50.0	44.0	40.0	39.0
ACR-N according to Standard [db/100m]	62.5	54.4	47.4	33.4	26.2	8.3	-10.4	
Typical ACR-N Values [db/100m]	78.0	70.0	64.0	54.0	50.0	45.0	40.0	39.0



Corning Optical Communications GmbH & Co. KG • Lelpziger Strasse 121 • 10117 Berlin, Germany
 +00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2022 Corning Optical Communications. All rights reserved.

Specifications

Environmental Conditions

Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, B2ca 4P, Green

CORNING

General Specifications

Environment	Indoor
Category	6A
Cable type	F/UTP
Bandwidth	550 MHz
Halogen-free	Yes
Construction	Simplex, 4P
Reaction to fire	B2ca, s1a, d0, a1
Legacy Part Number	VOL6AFL4500
Brand	Everon™

Cable Design

Conductor	Copper Wire, AWG 24/1
Conductor insulation	Solid PE
Twisting	2 cores to a pair
Outer jacket material	LSZH™/FRNC
Outer jacket colour	Green

Mechanical Characteristics

Fire load	630 MJ/km
Nominal outer diameter	7.5 mm
Min. bend radius installation	8x Cable-Ø
Maximum tensile strength	80 N

Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	45 ns/100 m
Max. loop resistance	190 Ω/km

Everon™ Copper Datacom F/UTP 550/24, Category 6A, LSZH™/FRNC, B2ca 4P, Green



Electrical Characteristics

Propagation delay	545 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Surface transfer impedance	10 mΩ
Propagation velocity at >10 MHz (NVP*c)	69 %
Coupling attenuation	55 dB
Insulation Resistance	> 5000 MΩ*km

Ordering Information